

GT55 NI

Commercial Door

One of the most secure swing doors available on the market today, the GT55 NI has been specifically designed for high traffic environments where no insulation is required. This makes it a very robust and highly cost-effective choice when specifying applications such as shopping complexes and retail centres that require significant partitioning without the need for thermal insulation.

The GT55 NI can be easily integrated with our ground floor treatment system and is available in single colour options, with a choice of polyester powder coating and anodised finishes. A full range of security and customisable hardware is also available to suit the specific demands of your design.



DESIGN FEATURES

- › Pocket or bead glazed for ease of site glazing
- › 110mm frame depth to accommodate varying types of applications
- › Slim 55mm frame profile for increased glass appearance
- › Ladder frame construction to enable easy on-site installation
- › Fully compatible with other AluK systems
- › Mullion drainage

OPTIONS

- › Can accommodate 6mm–28mm sealed units for acoustic performance
- › Wide range of hardware available offering full customisation
- › Available in single colour polyester powder coating, texture and anodised finishes
- › Internal and external screen application available


SPECIFICATIONS

	SINGLE	DOUBLE	GT55 NI SCREENING
PERFORMANCE AND ACCREDITATIONS			
U-Value (Double Glazing) (Ug: 1.0 W/m²K)	3.6 W/m²K	3.0 W/m²K	2.0 W/m²K
U-Value (Triple Glazing) (Ug: 0.7 W/m²K)	3.4 W/m²K	2.8 W/m²K	1.7 W/m²K
Air Permeability	-	-	Class 4 (600 Pa)
Water Tightness	-	-	Class 8A (450 Pa)
Wind Resistance	-	-	Class 5 (2000 Pa)
Durability EN 1191 Category	50,000 Cycles	50,000 Cycles	-
SYSTEM			
Depth	110mm	110mm	110mm
SIZE AND WEIGHT LIMITS			
Maximum Door Leaf Size (mm)	1250w x 2400h	2500w x 2400h	-
Maximum Door Leaf Weight	80kg	80kg	-
GLAZING			
Glazing Thickness (Single Glazing)	6mm - 12mm	6mm - 12mm	6mm - 12mm
Glazing Thickness (Double Glazing)	24mm - 28mm	24mm - 28mm	24mm - 28mm
SYSTEM FEATURES			
Single Colour	✓	✓	✓
Dual Colour	x	x	x
Textured Finish	✓	✓	✓
Anodised Finish	✓	✓	✓
Fire Exit option	✓	✓	✓
Part M compliant low threshold	✓	✓	-
Anti-Finger Trap	✓	✓	-
Sightlines	144mm	176mm	55mm
Mid-Rail and Lay Bar	✓	✓	✓
Panel Door	✓	✓	-
Single Point Locking	✓	✓	-
Concealed Hinges	✓	✓	-
Barrel Hinges	✓	✓	-
Electro Mechanical Locking	✓	✓	-
Automatic Door	✓	✓	-
APPLICATIONS			
New Build - Residential	✓	x	x
New Build - Commercial	✓	✓	✓
Refurbishment	✓	✓	✓
Heavy Commercial	✓	✓	✓

CAD CROSS SECTIONS AND THERMAL PROFILE

Additional details are available on request.


GT55 NI Jamb Locking Stile




GT55 NI Meeting Stile




GT55 NI Screen Cill




GT55 NI Screen Mullion



GT55 NI Jamb Anti Finger



GT55 NI Door on Low Threshold



GT55 NI Thermal Profile

